



**SPECIFICATIONS**

Current Rating: 0.3A AC,DC  
 Voltage Rating: 100V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 40mΩ Max.  
 Insulation Resistance: 1000MΩ Min.  
 Withstanding Voltage: 250V AC/minute  
 Pin Material: Phosphor Bronze/Gold-plated 3u”  
 Shell: Phosphor Bronze/Tin-plated  
 Material: LCP,UL94V-0  
 Color: Natural(Black)

**Ordering Information & Dimensions**

PART NO.	Dimensions				
	A	B	C	D	E
A0400WRA-SF-30P	11.60	16.40	14.00	16.80	16.10
A0400WRA-SF-40P	15.60	20.40	18.00	20.80	20.10

			UNIT	SCALE	SHEET	TITLE:
			mm		1 of 2	<b>0.40mm PITCH          90° WAFER-SMT TYPE,          WITH LOCK, WITH BOSS</b>
			DRAWN BY	APPROVED BY		
			童冠銘	董正一		
			2009.02.05	2009.02.05		
			GENERAL TOLERANCE			
			X.X±0.25	ANGLE±		
A0	NEW RELEASE	2009.02.05	X.XX±0.15			
REV.	DESCRIPTION	DATE	X.XXX±0.05			
			DRAW NO. :		REV.	
			A0400WRA-SF-XP		A0	