



**SPECIFICATIONS**

Current Rating: 1A AC,DC  
 Voltage Rating: 50V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 20mΩ Max.  
 Insulation Resistance: 100MΩ Min.  
 Withstanding Voltage: 500V AC/minute  
 Material: PBT,UL94V-0  
 Color: Natural(White)

**Ordering Information & Dimensions**

PART NO.	Dimensions	
	A	B
A1001H-02P-1	1.00	5.00
A1001H-03P-1	2.00	6.00
A1001H-04P-1	3.00	7.00
A1001H-05P-1	4.00	8.00
A1001H-06P-1	5.00	9.00
A1001H-07P-1	6.00	10.00
A1001H-08P-1	7.00	11.00
A1001H-09P-1	8.00	12.00
A1001H-10P-1	9.00	13.00
A1001H-11P-1	10.00	14.00
A1001H-12P-1	11.00	15.00
A1001H-13P-1	12.00	16.00
A1001H-14P-1	13.00	17.00
A1001H-15P-1	14.00	18.00
A1001H-16P-1	15.00	19.00
A1001H-17P-1	16.00	20.00
A1001H-18P-1	17.00	21.00
A1001H-19P-1	18.00	22.00
A1001H-20P-1	19.00	23.00

				UNIT: mm    SCALE:    SHEET: 1 of 1		<b>TITLE:</b> 1.00mm PITCH HOUSING WITH PROTRUSIONS
				DRAWN BY: 董正一    APPROVED BY: 董正一 2001.03.27    2001.03.27		
B2		REVISION		DATE		
B1		REVISION		DATE		
B0		NEW RELEASE		DATE		
REV.		DESCRIPTION		DATE		
		GENERAL TOLERANCE		ANGLE±		
		X. X±0.25		X. XX±0.15		
		X. XXX±0.05				
				DRAW NO.:		REV. B2
				A1001H-XP-1		