



**SPECIFICATIONS**

Current Rating: 1A AC,DC  
 Voltage Rating: 50V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 20mΩ Max.  
 Insulation Resistance: 100MΩ Min.  
 Withstanding Voltage: 500V AC/minute  
 Material: PBT,UL94V-0  
 Color: Natural(White)

**Ordering Information & Dimensions**

PART NO.	Dimensions	
	A	B
A1001H-02P-2	1.00	3.00
A1001H-03P-2	2.00	4.00
A1001H-04P-2	3.00	5.00
A1001H-05P-2	4.00	6.00
A1001H-06P-2	5.00	7.00
A1001H-07P-2	6.00	8.00
A1001H-08P-2	7.00	9.00
A1001H-09P-2	8.00	10.00
A1001H-10P-2	9.00	11.00
A1001H-11P-2	10.00	12.00
A1001H-12P-2	11.00	13.00
A1001H-13P-2	12.00	14.00
A1001H-14P-2	13.00	15.00
A1001H-15P-2	14.00	16.00
A1001H-16P-2	15.00	17.00
A1001H-17P-2	16.00	18.00
A1001H-18P-2	17.00	19.00
A1001H-19P-2	18.00	20.00
A1001H-20P-2	19.00	21.00

					JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
			UNIT	SCALE	SHEET	TITLE:
			mm		1 of 1	1.00mm PITCH HOUSING WITHOUT PROTRUSIONS
			DRAWN BY 董正一 2001.03.27	APPROVED BY 董正一 2001.03.27		
B2	REVISE	2007.06.14	GENERAL TOLERANCE			
B1	REVISE	2006.10.10	X. X±0.25	ANGLE±		
B0	NEW RELEASE	2006.04.14	X. XX±0.15			
REV.	DESCRIPTION	DATE	X. XXX±0.05			
					DRAW NO.:	REV.
					A1001H-XP-2	B2