



SPECIFICATIONS

Current Rating: 1A AC,DC
 Voltage Rating: 100V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 30mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Shell: Phosphor Bronze/Tin-plated
 Pin: Phosphor Bronze/Gold-plated
 Material: Nylon 6T,UL94V-0
 Color: Natural(Beige)

Ordering Information & Dimensions

PART NO.	Dimensions		
	A	B	C
A1007WR-S-08P	7.00	11.55	11.95
A1007WR-S-14P	13.00	17.55	17.95
A1007WR-S-20P	19.00	23.55	23.95
A1007WR-S-30P	29.00	33.55	33.95

			UNIT	SCALE	SHEET	TITLE:	
			mm		1 of 1		
			DRAWN BY	APPROVED BY		1.00mm PITCH 90° WAFER-SMT TYPE	
			董正一	董正一			
			2003.04.22	2003.04.22			
			GENERAL TOLERANCE				
			X.X±0.25	ANGLE±		DRAW NO. : A1007WR-S-XP	
B0	NEW RELEASE	2006.06.12	X.XX±0.15				REV. B0
REV.	DESCRIPTION	DATE	X.XXX±0.05				