



**SPECIFICATIONS**

Current Rating: 1A AC,DC  
 Voltage Rating: 150V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 30mΩ Max.  
 Insulation Resistance: 500MΩ Min.  
 Withstanding Voltage: 500V AC/minute  
 Material: Nylon 66,UL94V-0  
 Pantone Color: 7529C~7530C

**Ordering Information & Dimensions**

PART NO.	Dimensions	
	A	B
A1252H-02P	1.25	4.15
A1252H-03P	2.50	5.40
A1252H-04P	3.75	6.65
A1252H-05P	5.00	7.90
A1252H-06P	6.25	9.15
A1252H-07P	7.50	10.40
A1252H-08P	8.75	11.65
A1252H-09P	10.00	12.90
A1252H-10P	11.25	14.15
A1252H-11P	12.50	15.40
A1252H-12P	13.75	16.65
A1252H-13P	15.00	17.90
A1252H-14P	16.25	19.15
A1252H-15P	17.50	20.40

				JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
		UNIT	SCALE	SHEET	TITLE:
		mm		1 of 1	<b>1.25mm PITCH          SINGLE ROW HOUSING</b>
		DRAWN BY		APPROVED BY	
		董正一		董正一	
		2001.02.01		2001.02.01	
		GENERAL TOLERANCE			
B1	REVISE	2006.12.27	X. X±0.25	ANGLE±	DRAW NO. : A1252H-XP
B0	NEW RELEASE	2006.05.31	X. XX±0.15		
REV.	DESCRIPTION	DATE	X. XXX±0.05		
					REV. B1