



SPECIFICATIONS
 Current Rating: 4A AC,DC
 Voltage Rating: 125V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 1000V AC/minute
 Pin Material: Brass/Gold-flash 1~3u"
 Material: Nylon 46,UL94V-0
 Color: Natural(Beige)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A2013WV-02P46G	2.00	5.96
A2013WV-03P46G	4.00	7.96
A2013WV-04P46G	6.00	9.96
A2013WV-05P46G	8.00	11.96
A2013WV-06P46G	10.00	13.96
A2013WV-07P46G	12.00	15.96
A2013WV-08P46G	14.00	17.96
A2013WV-09P46G	16.00	19.96
A2013WV-10P46G	18.00	21.96
A2013WV-11P46G	20.00	23.96
A2013WV-12P46G	22.00	25.96
A2013WV-13P46G	24.00	27.96
A2013WV-14P46G	26.00	29.96
A2013WV-15P46G	28.00	31.96

			UNIT	SCALE	SHEET
			mm		1 of 1
			DRAWN BY		APPROVED BY
			朱恆秀		董正一
			2008.02.22		2008.02.22
			GENERAL TOLERANCE		
A1	ECN NO. EN0911040539	2009.11.04	X. X±0.25	ANGLE±	
A0	NEW RELEASE	2008.02.22	X. XX±0.15		
REV.	DESCRIPTION	DATE	X. XXX±0.05		
			TITLE:		
			2.00mm PITCH 180° WAFER, NYLON 46, GOLD-FLASH		
			DRAW NO. :		REV.
			A2013WV-XP46G		A1