



### SPECIFICATIONS

Current Rating: 3A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range:  $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$   
 Contact Resistance: 10m $\Omega$  Max  
 Insulation Resistance: 1000M $\Omega$  Min  
 Withstanding Voltage: 800V AC/minute  
 Material: Nylon 66,UL94V-0  
 Color: Natural(White)

### Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A2502H-02P	2.50	7.00
A2502H-03P	5.00	9.50
A2502H-04P	7.50	12.00
A2502H-05P	10.00	14.50
A2502H-06P	12.50	17.00
A2502H-07P	15.00	19.50
A2502H-08P	17.50	22.00
A2502H-09P	20.00	24.50
A2502H-10P	22.50	27.00
A2502H-11P	25.00	29.50
A2502H-12P	27.50	32.00
A2502H-13P	30.00	34.50
A2502H-14P	32.50	37.00
A2502H-15P	35.00	39.50

						<b>JOINT TECH ELECTRONIC IND. CO., LTD.</b> <b>JOY DAY INDUSTRIAL CO., LTD.</b>		
		UNIT	SCALE	SHEET	TITLE:			
		mm		1 of 1	<b>2.50mm PITCH HOUSING</b>  DRAW NO. : A2502H-XP      REV. B0			
		DRAWN BY		APPROVED BY				
		董正一		董正一				
		2001.02.01		2001.02.01				
		GENERAL TOLERANCE						
		X. X $\pm$ 0.25		ANGLE $\pm$				
B0		NEW RELEASE		2006.05.14		X. XX $\pm$ 0.15		
REV.		DESCRIPTION		DATE		X. XXX $\pm$ 0.05		