



SPECIFICATIONS

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1000V AC/minute
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A2508H-02P	2.50	7.30
A2508H-03P	5.00	9.80
A2508H-04P	7.50	12.30
A2508H-05P	10.00	14.80
A2508H-06P	12.50	17.30
A2508H-07P	15.00	19.80
A2508H-08P	17.50	22.30
A2508H-09P	20.00	24.80
A2508H-10P	22.50	27.30
A2508H-11P	25.00	29.80
A2508H-12P	27.50	32.30
A2508H-13P	30.00	34.80
A2508H-14P	32.50	37.30
A2508H-15P	35.00	39.80
A2508H-20P	47.50	52.30

				JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
UNIT	SCALE	SHEET	TITLE:		
mm		1 of 1	2.50mm PITCH HOUSING		
DRAWN BY 歐陽小強 2007.08.23		APPROVED BY 謝瑞清 2007.08.23			
GENERAL TOLERANCE			DRW NO.: A2508H-XP		
X. X±0.25		ANGLE±			
A0	NEW RELEASE	2007.08.23	X. XX±0.15	REV. A0	
REV.	DESCRIPTION	DATE	X. XXX±0.05		