


SPECIFICATIONS

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 500MΩ Min
 Withstanding Voltage: 800V AC/minute
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

PART NO.	Dimensions		
	A	B	C
A2540H-02P	2.50	7.25	5.90
A2540H-03P	5.00	9.75	8.40
A2540H-04P	7.50	12.25	10.90
A2540H-05P	10.00	14.75	13.40
A2540H-06P	12.50	17.25	15.90
A2540H-07P	15.00	19.75	18.40
A2540H-08P	17.50	22.25	20.90
A2540H-09P	20.00	24.75	23.40
A2540H-10P	22.50	27.25	25.90
A2540H-11P	25.00	29.75	28.40
A2540H-12P	27.50	32.25	30.90
A2540H-13P	30.00	34.75	33.40
A2540H-14P	32.50	37.25	35.90
A2540H-15P	35.00	39.75	38.40

		 JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
	UNIT	SCALE	SHEET
	mm		1 of 1
	DRAWN BY	APPROVED BY	
	董正一	董正一	
B3	REVISE	2006.10.23	2001.02.01
B2	REVISE	2006.09.18	2001.02.01
B1	REVISE	2006.05.15	GENERAL TOLERANCE
B0	NEW RELEASE	2005.12.23	ANGLE±
REV.	DESCRIPTION	DATE	X.XX±0.15 X.XXX±0.05
			TITLE:
			2.50mm PITCH HOUSING
DRAW NO.:			REV.
A2540H-XP			B3