


TYPE 2



SPECIFICATIONS

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 500MΩ Min
 Withstanding Voltage: 800V AC/minute
 Pin Material: Brass/Tin-plated
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A2540WR-02P2	2.50	5.00
A2540WR-03P2	5.00	7.50
A2540WR-04P2	7.50	10.00
A2540WR-05P2	10.00	12.50
A2540WR-06P2	12.50	15.00
A2540WR-07P2	15.00	17.50
A2540WR-08P2	17.50	20.00
A2540WR-09P2	20.00	22.50
A2540WR-10P2	22.50	25.00
A2540WR-11P2	25.00	27.50
A2540WR-12P2	27.50	30.00
A2540WR-13P2	30.00	32.50
A2540WR-14P2	32.50	35.00
A2540WR-15P2	35.00	37.50

UNIT	SCALE	SHEET	TITLE:
mm		1 of 1	2.50mm PITCH 90° WAFER
DRAWN BY 李勤		APPROVED BY 董正一	
		2005.12.23	
GENERAL TOLERANCE			
A2	REVISE	2006.09.18	
A1	REVISE	2006.05.15	X. X±0.25
A0	NEW RELEASE	2005.12.23	X. XX±0.15
REV.	DESCRIPTION	DATE	X. XXX±0.05
			DRW NO. : A2540WR-XP2
			REV. A2