



SEC:D-D

Ordering Information & Specifications

| Part No | Wire Range | Insulation O.D. | Material | Finish | Qty/reel |
|-----------|------------|-----------------|-----------------|------------|-----------|
| A2541-HPE | AWG#22-#26 | 1.63mm(max) | Phosphor Bronze | Gold-flash | 10,000pcs |
| A2541-HBE | AWG#22-#26 | 1.63mm(max) | Brass | Gold-flash | |
| A2541-TPE | AWG#22-#26 | 1.63mm(max) | Phosphor Bronze | Tin-plated | |
| A2541-TBE | AWG#22-#26 | 1.63mm(max) | Brass | Tin-plated | |

Note:E-Stamping before Tin-plated or Gold-flash

| | | | | | |
|-------------------------------|-------------|----------------------------------|--------------------------------|--|--|
| | | | | JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD. | |
| UNIT | SCALE | SHEET | TITLE: | | |
| mm | | 1 of 1 | 2.54mm PITCH CRIMP TERMINAL | | |
| DRAWN BY 董正一 2001.02.01 | | APPROVED BY 董正一 2001.02.01 | | | |
| GENERAL TOLERANCE | | | | | |
| | | X. X±0.25 | ANGLE± | | |
| BO | NEW RELEASE | 2006.04.10 | X. XX±0.15 | DRAW NO. : A2541-XX | |
| REV. | DESCRIPTION | DATE | X. XXX±0.05 | | |