



SPECIFICATIONS

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Material: PBT30%GF,UL94V-0
 Color: Natural(Black)

Ordering Information & Dimensions

Ordering Information:
 A2541H-M-XP-*
 1 2

- 1.Series No.
 2.Style:
 1-Type 1
 2-Type 2

PART NO.	Dimensions	
	A	B
A2541H-M-02P	2.54	5.08
A2541H-M-03P	5.08	7.62
A2541H-M-04P	7.62	10.16
A2541H-M-05P	10.16	12.70
A2541H-M-06P	12.70	15.24
A2541H-M-07P	15.24	17.78
A2541H-M-08P	17.78	20.32
A2541H-M-09P	20.32	22.86
A2541H-M-10P	22.86	25.40
A2541H-M-11P	25.40	27.94
A2541H-M-12P	27.94	30.48

				JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.				
UNIT	SCALE	SHEET	TITLE:					
mm		1 of 1	2.54mm PITCH HOUSING					
DRAWN BY	APPROVED BY					DRAW NO. : A2541H-M-XP-X		
董正一	董正一							
2001.02.01	2001.02.01					REV. BO		
GENERAL TOLERANCE			REV. BO					
X. X±0.25	ANGLE±					REV. BO		
X. XX±0.15			REV. BO					
X. XXX±0.05						REV. BO		
BO	NEW RELEASE	2006.04.10	REV. BO					
REV.	DESCRIPTION	DATE				REV. BO		