



SPECIFICATIONS

Current Rating: 4A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1000V AC/minute
 Material: Nylon 66,UL94V-2
 Pantone Color: 1685C

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A2542HA-02P	2.54	5.68
A2542HA-03P	5.08	8.22
A2542HA-04P	7.62	10.76
A2542HA-05P	10.16	13.30
A2542HA-06P	12.70	15.84
A2542HA-07P	15.24	18.38
A2542HA-08P	17.78	20.92
A2542HA-09P	20.32	23.46
A2542HA-10P	22.86	26.00
A2542HA-11P	25.40	28.54
A2542HA-12P	27.94	31.08
A2542HA-13P	30.48	33.62
A2542HA-14P	33.02	36.16
A2542HA-15P	35.56	38.70
A2542HA-16P	38.10	41.24
A2542HA-17P	40.64	43.78
A2542HA-18P	43.18	46.32
A2542HA-19P	45.72	48.86
A2542HA-20P	48.26	51.40

		UNIT	SCALE
		mm	1 of 1
		DRAWN BY	APPROVED BY
		董正一	董正一
		2001.02.01	2001.02.01
		GENERAL TOLERANCE	
		X. X±0.25	ANGLE±
		X. XX±0.15	
		X. XXX±0.05	
BO	NEW RELEASE	2006.05.09	
REV.	DESCRIPTION	DATE	
			TITLE:
			2.54mm PITCH HOUSING
			DRAW NO. :
			A2542HA-XP
			REV. BO