

Ordering Information:
A2542WRA-XP*


1 2

1.Part No.

2.Style:

1-Type 1

2-Type 2



SPECIFICATIONS

Current Rating: 4A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -25°C ~ +85°C

Contact Resistance: 10mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 1000V AC/minute

Pin Material: Brass/Tin-plated

Material: Nylon 66,UL94V-2

Pantone Color: 1685C

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A2542WRA-02P	2.54	5.08
A2542WRA-03P	5.08	7.62
A2542WRA-04P	7.62	10.16
A2542WRA-05P	10.16	12.70
A2542WRA-06P	12.70	15.24
A2542WRA-07P	15.24	17.78
A2542WRA-08P	17.78	20.32
A2542WRA-09P	20.32	22.86
A2542WRA-10P	22.86	25.40
A2542WRA-11P	25.40	27.94
A2542WRA-12P	27.94	30.48
A2542WRA-13P	30.48	33.02
A2542WRA-14P	33.02	35.56
A2542WRA-15P	35.56	38.10
A2542WRA-16P	38.10	40.64
A2542WRA-17P	40.64	43.18
A2542WRA-18P	43.18	45.72
A2542WRA-19P	45.72	48.26
A2542WRA-20P	48.26	50.80



JOINT TECH ELECTRONIC IND. CO., LTD.

JOY DAY INDUSTRIAL CO., LTD.

UNIT SCALE SHEET
mm 1 of 1

DRAWN BY 董正一
2001.02.01

APPROVED BY 董正一
2001.02.01

GENERAL TOLERANCE

REV.	DESCRIPTION	DATE	X.X±0.25	ANGLE±
B1	REVISE	2006.06.06	X.X±0.25	ANGLE±
B0	NEW RELEASE	2006.05.09	X.XX±0.15	
			X.XXX±0.05	

TITLE:
2.54mm PITCH
90° WAFER
DRAW NO. : A2542WRA-XPX

REV. B1