



Ordering code

A2545 H-XP XXX
 ① ② ③ ④

① Series No.
 ② Connector type: H=Housing
 ③ No. of circuits
 ④ Option code:
 Blank=PBT,UL94V-0, Color: Natural(Black)
 -WH=PBT,UL94V-0, Color: Natural(White)
 -NF=PA6,UL94V-2 NO FLAME
 IEC 60335-1 rev. 4, Color: Natural(Beige)

SPECIFICATIONS
 Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 1500V AC/minute

Circuit No.	Dimensions		Circuit No.	Dimensions	
	A	B		A	B
01P	---	2.54	21P	50.80	53.34
02P	2.54	5.08	22P	53.34	55.88
03P	5.08	7.62	23P	55.88	58.42
04P	7.62	10.16	24P	58.42	60.96
05P	10.16	12.70	25P	60.96	63.50
06P	12.70	15.24	26P	63.50	66.04
07P	15.24	17.78	27P	66.04	68.58
08P	17.78	20.32	28P	68.58	71.12
09P	20.32	22.86	29P	71.12	73.66
10P	22.86	25.40	30P	73.66	76.20
11P	25.40	27.94	31P	76.20	78.74
12P	27.94	30.48	32P	78.74	81.28
13P	30.48	33.02	33P	81.28	83.82
14P	33.02	35.56	34P	83.82	86.36
15P	35.56	38.10	35P	86.36	88.90
16P	38.10	40.64	36P	88.90	91.44
17P	40.64	43.18	37P	91.44	93.98
18P	43.18	45.72	38P	93.98	96.52
19P	45.72	48.26	39P	96.52	99.06
20P	48.26	50.80	40P	99.06	101.60

 燦達電子工業股份有限公司 JOINT TECH ELECTRONIC IND. CO., LTD.			
UNIT	SCALE	SHEET	TITLE:
mm		1 of 1	
DRAWN BY	APPROVED BY		2.54mm PITCH SINGLE ROW HOUSING
董正一	董正一		
2001.02.01	2001.02.01		
GENERAL TOLERANCE			DRAW NO. : A2545H-XP
X. X±0.25	ANGLE±		
X. XX±0.15			REV. B4
X. XXX±0.05			
B4	EN1001280069	2010.01.28	
REV.	DESCRIPTION	DATE	