



Ordering code

<b>A3961 H-XP XXX</b>			
①	②	③	④
① Series No.			
② Connector type: H=Housing			
③ No. of circuits			
④ Option code:			
Blank=Nylon 66,UL94V-0, Color: Natural(White)			
-RD =Nylon 66,UL94V-0, Color: Red Pantone color: 1785C			
-BL =Nylon 66,UL94V-0, Color: Blue Pantone color: 660C			
-BK =Nylon 66,UL94V-0, Color: Natural(Black)			
-PU =Nylon 66,UL94V-0, Color: Lavender Pantone color: 2583C			
-NF =PA6,UL94V-2 NO FLAME IEC 60335-1 rev. 4, Color: Natural(Beige)			
-101=PA6,UL94V-2 NO FLAME IEC 60335-1 rev. 4, Color: Red			
-102=PA6,UL94V-2 NO FLAME IEC 60335-1 rev. 4, Color: Black			

SPECIFICATIONS

Current Rating: 7A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 10mΩ Max.  
 Insulation Resistance: 1000MΩ Min.  
 Withstanding Voltage: 1500V AC/minute

Circuit No.	Dimensions		Circuit No.	Dimensions	
	A	B		A	B
02P	3.96	8.02	09P	31.68	35.74
03P	7.92	11.98	10P	35.64	39.70
04P	11.88	15.94	11P	39.60	43.66
05P	15.84	19.90	12P	43.56	47.62
06P	19.80	23.86	13P	47.52	51.58
07P	23.76	27.82	14P	51.48	55.54
08P	27.72	31.78	15P	55.44	59.50

					JOINT TECH ELECTRONIC IND. CO., LTD.		TITLE:	
			UNIT	SCALE	SHEET	3.96mm PITCH HOUSING		
			mm		1 of 1			
			DRAWN BY		APPROVED BY		DRAW NO. : A3961H-XP	
			董正一		董正一			
			2001.02.01		2001.02.01			
			GENERAL TOLERANCE					
			X. X±0.25		ANGLE±			
B3	EN1001130025	2010.01.13	X. XX±0.15				REV. B3	
B2	REVISE	2007.12.08	X. XXX±0.05					
B1	REVISE	2007.01.09						
B0	NEW RELEASE	2006.04.17						
REV.	DESCRIPTION	DATE						