



SPECIFICATIONS

Current Rating: 7A AC,DC
 Voltage Rating: 600V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 3mΩ Max
 Insulation Resistance: 5000MΩ Min
 Withstanding Voltage: 2200V AC/minute
 Pin Material: Brass/Tin-plated
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A3963WR-02P	3.96	7.92
A3963WR-03P	7.92	11.88
A3963WR-04P	11.88	15.84
A3963WR-05P	15.84	19.80
A3963WR-06P	19.80	23.76
A3963WR-07P	23.76	27.72
A3963WR-08P	27.72	31.68
A3963WR-09P	31.68	35.64
A3963WR-10P	35.64	39.60
A3963WR-11P	39.60	43.56
A3963WR-12P	43.56	47.52
A3963WR-13P	47.52	51.48
A3963WR-14P	51.48	55.44
A3963WR-15P	55.44	59.40
A3963WR-16P	59.40	63.36
A3963WR-17P	63.36	67.32
A3963WR-18P	67.32	71.28
A3963WR-19P	71.28	75.24
A3963WR-20P	75.24	79.20

		UNIT	SCALE
		mm	1 of 1
		DRAWN BY	APPROVED BY
		李勤	董正一
		2005.12.05	2005.12.05
GENERAL TOLERANCE			
A1	REVISE	2006.04.28	X. X±0.25
A0	NEW RELEASE	2005.12.05	X. XX±0.15
REV.	DESCRIPTION	DATE	X. XXX±0.05
		TITLE:	
		3.96mm PITCH 90° WAFER	
		DRAW NO. :	REV.
		A3963WR-XP	A1