



SPECIFICATIONS

Current Rating: 7A AC,DC
 Voltage Rating: 600V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 3mΩ Max
 Insulation Resistance: 5000MΩ Min
 Withstanding Voltage: 2200V AC/minute
 Pin Material: Brass/Tin-plated
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A3963WV-02PR	3.96	7.92
A3963WV-03PR	7.92	11.88
A3963WV-04PR	11.88	15.84
A3963WV-05PR	15.84	19.80
A3963WV-06PR	19.80	23.76
A3963WV-07PR	23.76	27.72
A3963WV-08PR	27.72	31.68
A3963WV-09PR	31.68	35.64
A3963WV-10PR	35.64	39.60
A3963WV-11PR	39.60	43.56
A3963WV-12PR	43.56	47.52
A3963WV-13PR	47.52	51.48
A3963WV-14PR	51.48	55.44
A3963WV-15PR	55.44	59.40
A3963WV-16PR	59.40	63.36
A3963WV-17PR	63.36	67.32
A3963WV-18PR	67.32	71.28
A3963WV-19PR	71.28	75.24
A3963WV-20PR	75.24	79.20

				UNIT	SCALE	SHEET	TITLE:
				mm		1 of 1	
DRAWN BY		APPROVED BY		3.96mm PITCH 180° WAFER, ROUND PIN			
李勤		董正一					
2005.12.05		2005.12.05					
GENERAL TOLERANCE							
A1	REVISE	2006.04.28	X. X±0.25	ANGLE±	DRAW NO. : A3963WV-XPR REV. A1		
A0	NEW RELEASE	2005.12.05	X. XX±0.15				
REV.	DESCRIPTION	DATE	X. XXX±0.05				