



Ordering code

<b>B3965 HV-F-XP</b>				
①	②	③	④	
① Series No.				
② Connector type: HV=Housing Vertical type				
③ Mounting type: F=DIP with boss				
④ No. of circuits				

**SPECIFICATIONS**  
 Current Rating: 7A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 10mΩ Max.  
 Insulation Resistance: 1000MΩ Min.  
 Withstanding Voltage: 1500V AC/minute  
 Material: Nylon 66,UL94V-0  
 Color: Natural(White)

Circuit No.	Dimensions		Circuit No.	Dimensions	
	A	B		A	B
02P	3.96	8.96	09P	31.68	36.68
03P	7.92	12.92	10P	35.64	40.64
04P	11.88	16.88	11P	39.60	44.60
05P	15.84	20.84	12P	43.56	48.56
06P	19.80	24.80	13P	47.52	52.52
07P	23.76	28.76	14P	51.48	56.48
08P	27.72	32.72	15P	55.44	60.44

 <b>燦達電子工業股份有限公司</b> <b>JOINT TECH ELECTRONIC IND. CO., LTD.</b>			UNIT SCALE SHEET mm 1 of 1		TITLE:  <b>3.96mm PITCH          180° HOUSING,          WITH POLARIZING BOSS</b>	
DRAWN BY		APPROVED BY				
董正一		董正一		DRAW NO. : B3965HV-F-XP		REV. B2
2003.09.02		2003.09.02				
B2	EN1001050015	2010.01.04	GENERAL TOLERANCE			
B1	REVISE	2006.08.08	X. X±0.25	ANGLE±		
B0	NEW RELEASE	2005.12.06	X. XX±0.15			
REV.	DESCRIPTION	DATE	X. XXX±0.05			