

Ordering code


**B3965 HV-XP**

①    ②    ③

① Series No.  
 ② Connector type: HV=Housing Vertical type  
 ③ No. of circuits

**SPECIFICATIONS**  
 Current Rating: 7A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 10mΩ Max.  
 Insulation Resistance: 1000MΩ Min.  
 Withstanding Voltage: 1500V AC/minute  
 Material: Nylon 66,UL94V-0  
 Color: Natural(White)

Circuit No.	Dimensions		Circuit No.	Dimensions	
	A	B		A	B
02P	3.96	8.96	09P	31.68	36.68
03P	7.92	12.92	10P	35.64	40.64
04P	11.88	16.88	11P	39.60	44.60
05P	15.84	20.84	12P	43.56	48.56
06P	19.80	24.80	13P	47.52	52.52
07P	23.76	28.76	14P	51.48	56.48
08P	27.72	32.72	15P	55.44	60.44

 <b>燦達電子工業股份有限公司</b> <b>JOINT TECH ELECTRONIC IND. CO., LTD.</b>			<b>TITLE:</b> <b>3.96mm PITCH</b> <b>180° HOUSING,</b> <b>WITHOUT POLARIZING BOSS</b>	
UNIT	SCALE	SHEET	DRAW NO. : B3965HV-XP	
mm		1 of 1		
DRAWN BY		APPROVED BY		
董正一		董正一		
2003.09.02		2003.09.02		
GENERAL TOLERANCE				
B2	EN1001050015	2010.01.04	ANGLE±	
B1	REVISE	2006.08.08	X.X±0.25	
B0	NEW RELEASE	2005.12.06	X.XX±0.15	
REV.	DESCRIPTION	DATE	X.XXX±0.05	