



SPECIFICATIONS

Current Rating: 7A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
B3965HV-02P	3.96	8.96
B3965HV-03P	7.92	12.92
B3965HV-04P	11.88	16.88
B3965HV-05P	15.84	20.84
B3965HV-06P	19.80	24.80
B3965HV-07P	23.76	28.76
B3965HV-08P	27.72	32.72
B3965HV-09P	31.68	36.68
B3965HV-10P	35.64	40.64
B3965HV-11P	39.60	44.60
B3965HV-12P	43.56	48.56
B3965HV-13P	47.52	52.52
B3965HV-14P	51.48	56.48
B3965HV-15P	55.44	60.44

		UNIT	SCALE
		mm	1 of 1
		TITLE:	
		3.96mm PITCH 180 HOUSING, WITHOUT POLARIZING BOSS	
		DRAWN BY	APPROVED BY
		董正一	董正一
		2003.09.02	2003.09.02
		GENERAL TOLERANCE	
B1	REVISE	2006.08.08	X.X ±0.25
B0	NEW RELEASE	2005.12.06	X.XX ±0.15
REV.	DESCRIPTION	DATE	X.XXX ±0.05
		ANGLE ±	
		DRAW NO.:	
		B3965HV-XP	
		REV. B1	