



SPECIFICATIONS
 Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1000V AC/minute
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
C2504HF-02P	2.50	6.00
C2504HF-03P	5.00	8.50
C2504HF-04P	7.50	11.00
C2504HF-05P	10.00	13.50
C2504HF-06P	12.50	16.00
C2504HF-07P	15.00	18.50
C2504HF-08P	17.50	21.00
C2504HF-09P	20.00	23.50
C2504HF-10P	22.50	26.00
C2504HF-11P	25.00	28.50
C2504HF-12P	27.50	31.00
C2504HF-13P	30.00	33.50
C2504HF-14P	32.50	36.00
C2504HF-15P	35.00	38.50
C2504HF-16P	37.50	41.00
C2504HF-17P	40.00	43.50
C2504HF-18P	42.50	46.00
C2504HF-19P	45.00	48.50
C2504HF-20P	47.50	51.00

				JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
		UNIT	SCALE	SHEET	TITLE:
		mm		1 of 1	2.50mm PITCH HOUSING-RECEPTACLE
		DRAWN BY	APPROVED BY		
		蕭惠風	董正一		
		2002.09.23	2002.09.23		
GENERAL TOLERANCE					
B1	REVISE	2006.11.10	X. X±0.25	ANGLE±	
B0	NEW RELEASE	2005.12.10	X. XX±0.15		
REV.	DESCRIPTION	DATE	X. XXX±0.05		
				DRW NO.:	REV. B1
				C2504HF-XP	