


SPECIFICATIONS

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1000V AC/minute
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

PART NO.	Dimensions		
	A	B	C
C2504HM-02P	2.50	8.60	5.80
C2504HM-03P	5.00	11.10	8.30
C2504HM-04P	7.50	13.60	10.80
C2504HM-05P	10.00	16.10	13.30
C2504HM-06P	12.50	18.60	15.80
C2504HM-07P	15.00	21.10	18.30
C2504HM-08P	17.50	23.60	20.80
C2504HM-09P	20.00	26.10	23.30
C2504HM-10P	22.50	28.60	25.80
C2504HM-11P	25.00	31.10	28.30
C2504HM-12P	27.50	33.60	30.80
C2504HM-13P	30.00	36.10	33.30
C2504HM-14P	32.50	38.60	35.80
C2504HM-15P	35.00	41.10	38.30
C2504HM-16P	37.50	43.60	40.80

		 JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
UNIT	SCALE	SHEET	TITLE:
mm		1 of 1	2.50mm PITCH HOUSING-PLUG
DRAWN BY 蕭惠風 2002.09.27		APPROVED BY 董正一 2002.09.27	
B2	REVISE	2007.03.30	GENERAL TOLERANCE
B1	REVISE	2006.11.10	X. X±0.25
B0	NEW RELEASE	2005.12.10	X. XX±0.15
REV.	DESCRIPTION	DATE	X. XXX±0.05
			DRW NO.: C2504HM-XP
			REV. B2