



### SPECIFICATIONS

Current Rating: 3A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range:  $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$

Contact Resistance:  $10\text{m}\Omega$  Max

Insulation Resistance:  $500\text{M}\Omega$  Min

Withstanding Voltage: 1500V AC/minute

Material: Nylon 66,UL94V-0

Color: Black

### Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
C2505HF-2P	2.50	5.50
C2505HF-3P	5.00	8.00
C2505HF-4P	7.50	10.50
C2505HF-5P	10.00	13.00
C2505HF-6P	12.50	15.50
C2505HF-7P	15.00	18.00
C2505HF-8P	17.50	20.50
C2505HF-9P	20.00	23.00
C2505HF-10P	22.50	25.50
C2505HF-11P	25.00	28.00
C2505HF-12P	27.50	30.50

				JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
		UNIT	SCALE	SHEET	TITLE:
		mm		1 of 1	<b>2.50mm PITCH HOUSING-RECEPTACLE</b>
		DRAWN BY	APPROVED BY		
		董正一	董正一		
		2001.02.01	2001.02.01		
GENERAL TOLERANCE					
B1	REVISE	2005.11.24	X. $\pm 0.25$	ANGLE±	DRAW NO. : C2505HF-XP
B0	NEW RELEASE	2005.10.17	X. $\text{XX} \pm 0.15$		
REV.	DESCRIPTION	DATE	X. $\text{XXX} \pm 0.05$		
					REV. B1