



SPECIFICATIONS

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 500MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Material: Nylon 66,UL94V-0
 Color: Black

Ordering Information & Dimensions

| PART NO. | Dimensions | |
|-------------|------------|-------|
| | A | B |
| C2505HM-2P | 2.50 | 8.00 |
| C2505HM-3P | 5.00 | 10.50 |
| C2505HM-4P | 7.50 | 13.00 |
| C2505HM-5P | 10.00 | 15.50 |
| C2505HM-6P | 12.50 | 18.00 |
| C2505HM-7P | 15.00 | 20.50 |
| C2505HM-8P | 17.50 | 23.00 |
| C2505HM-9P | 20.00 | 25.50 |
| C2505HM-10P | 22.50 | 28.00 |
| C2505HM-11P | 25.00 | 30.50 |
| C2505HM-12P | 27.50 | 33.00 |

| | | | | | |
|------|-------------|-------------------|-------------------|--|------------------------------|
| | | | | JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD. | |
| | | UNIT | SCALE | SHEET | TITLE: |
| | | mm | | 1 of 1 | 2.50mm PITCH HOUSING-PLUG |
| | | DRAWN BY | APPROVED BY | | |
| | | 董正一 2001.02.01 | 董正一 2001.02.01 | | |
| | | GENERAL TOLERANCE | | | |
| | | X. X±0.25 | ANGLE± | | DRAW NO. : C2505HM-XP |
| B0 | NEW RELEASE | 2005.10.17 | X. XX±0.15 | | |
| REV. | DESCRIPTION | DATE | X. XXX±0.05 | | |