



**SPECIFICATIONS**  
 Current Rating: 2A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 10mΩ Max  
 Insulation Resistance: 1000MΩ Min  
 Withstanding Voltage: 500V AC/minute  
 Material: PBT,UL94V-0  
 Color: Natural(Black)

**Ordering Information & Dimensions**

PART NO.	Dimensions	
	A	B
C2544HM-02P	2.54	7.11
C2544HM-03P	5.08	9.65
C2544HM-04P	7.62	12.19
C2544HM-05P	10.16	14.73
C2544HM-06P	12.70	17.27
C2544HM-07P	15.24	19.81
C2544HM-08P	17.78	22.35
C2544HM-09P	20.32	24.89
C2544HM-10P	22.86	27.43
C2544HM-11P	25.40	29.97
C2544HM-12P	27.94	32.51
C2544HM-13P	30.48	35.05
C2544HM-14P	33.02	37.59
C2544HM-15P	35.56	40.13

3.00±0.15

					JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.		
			UNIT	SCALE	SHEET	TITLE:	
			mm		1 of 1	2.54mm PITCH HOUSING	
			DRAWN BY	APPROVED BY			
			董正一	董正一			
			2007.11.21	2007.11.21			
			GENERAL TOLERANCE			DRAW NO. : C2544HM-XP	
			X. X±0.25	ANGLE±			
			X. XX±0.15				
			X. XXX±0.05				
A0	NEW RELEASE	2007.11.21					REV.
REV.	DESCRIPTION	DATE					A0