



SPECIFICATIONS

Current Rating: 5A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Material: Nylon 66,UL94V-2
 Color: Black

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
C3030HM-2P	3.00	6.85
C3030HM-3P	6.00	9.85
C3030HM-4P	9.00	12.85
C3030HM-5P	12.00	15.85
C3030HM-6P	15.00	18.85
C3030HM-7P	18.00	21.85
C3030HM-8P	21.00	24.85
C3030HM-9P	24.00	27.85
C3030HM-10P	27.00	30.85
C3030HM-11P	30.00	33.85
C3030HM-12P	33.00	36.85

				UNIT SCALE SHEET mm 1 of 1		TITLE: 3.00mm PITCH HOUSING-PLUG, SINGLE ROW, MICRO-FIT
				DRAWN BY APPROVED BY 董正一 董正一 2003.05.14 2003.05.14		
		GENERAL TOLERANCE		ANGLE±		DRAW NO. : C3030HM-XP
BO	NEW RELEASE	2005.12.14	X. X±0.25			
REV.	DESCRIPTION	DATE	X. XX±0.15			
			X. XXX±0.05			