



SPECIFICATIONS

Current Rating: 5A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Material: Nylon 66,UL94V-2
 Color: Black

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
C3030HMA-2P	3.00	6.85
C3030HMA-3P	6.00	9.85
C3030HMA-4P	9.00	12.85
C3030HMA-5P	12.00	15.85
C3030HMA-6P	15.00	18.85
C3030HMA-7P	18.00	21.85
C3030HMA-8P	21.00	24.85
C3030HMA-9P	24.00	27.85
C3030HMA-10P	27.00	30.85
C3030HMA-11P	30.00	33.85
C3030HMA-12P	33.00	36.85

				JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
		UNIT	SCALE	SHEET	TITLE:
		mm		1 of 1	3.00mm PITCH HOUSING-PLUG, SINGLE ROW, MICRO-FIT
		DRAWN BY	APPROVED BY		
		董正一	董正一		
		2004.09.16	2004.09.16		
		GENERAL TOLERANCE			
		X. X±0.25	ANGLE±		DRAW NO. : C3030HMA-XP
B0	NEW RELEASE	2005.12.14	X. XX±0.15		
REV.	DESCRIPTION	DATE	X. XXX±0.05		