



**SPECIFICATIONS**  
 Current Rating: 9A AC,DC  
 Voltage Rating: 600V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 10mΩ Max  
 Insulation Resistance: 1000MΩ Min  
 Withstanding Voltage: 1500V AC/minute  
 Material: Nylon 66,UL94V-2  
 Color: Natural(Translucent)

**Ordering Information & Dimensions**

PART NO.	Dimensions	
	A	B
C4255HMA-2X01P	---	5.40
C4255HMA-2X02P	4.20	9.60
C4255HMA-2X03P	8.40	13.80
C4255HMA-2X04P	12.60	18.00
C4255HMA-2X05P	16.80	22.20
C4255HMA-2X06P	21.00	26.40
C4255HMA-2X07P	25.20	30.60
C4255HMA-2X08P	29.40	34.80
C4255HMA-2X09P	33.60	39.00
C4255HMA-2X10P	37.80	43.20
C4255HMA-2X11P	42.00	47.40
C4255HMA-2X12P	46.20	51.60

			UNIT	SCALE	SHEET
			mm		1 of 1
			DRAWN BY		APPROVED BY
			李勤		董正一
			2006.06.07		2006.06.07
			GENERAL TOLERANCE		
			X. X±0.25	ANGLE±	
			X. XX±0.15	▽	
			X. XXX±0.05	⊕	
A0	NEW RELEASE	2006.06.07	DRAW NO. : C4255HMA-2XNP		
REV.	DESCRIPTION	DATE	REV. A0		

TITLE:  
 4.20mm PITCH  
 HOUSING-PLUG,  
 MINI-FIT