



SPECIFICATIONS

Current Rating: 15A AC,DC
 Voltage Rating: 600V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 3.5mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 5000V AC/minute
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
C6350HF-3X02P-V0	6.35	13.97
C6350HF-3X03P-V0	12.70	20.32
C6350HF-3X04P-V0	19.05	26.67
C6350HF-3X05P-V0	25.40	33.02

UNIT	SCALE	SHEET	TITLE:		
mm		1 of 1	6.35mm PITCH TRIPLE ROW HOUSING- RECEPTACLE		
DRAWN BY		APPROVED BY			
李勤		董正一			
2006.02.25		2006.02.25			
GENERAL TOLERANCE					
A1	REVISE	2007.09.14	X. X±0.25	ANGLE±	
A0	NEW RELEASE	2006.02.25	X. XX±0.15		
REV.	DESCRIPTION	DATE	X. XXX±0.05		
			DRW NO. :	REV. A1	
			C6350HF-3XNP-V0		

