



**SPECIFICATIONS**

Current Rating: 15A AC,DC  
 Voltage Rating: 600V AC,DC  
 Temperature Range:  $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$   
 Contact Resistance:  $3.5\text{m}\Omega$  Max  
 Insulation Resistance:  $1000\text{M}\Omega$  Min  
 Withstanding Voltage: 5000V AC/minute  
 Pin Material: Brass/Tin-plated  
 Material: Nylon 66,UL94V-0  
 Color: Natural(White)

**Ordering Information & Dimensions**

PART NO.	Dimensions	
	A	B
C6350WV-02PFV0	6.35	13.97
C6350WV-03PFV0	12.70	20.32
C6350WV-04PFV0	19.05	26.67
C6350WV-05PFV0	25.40	33.02
C6350WV-06PFV0	31.75	39.37
C6350WV-08PFV0	44.45	52.07

UNIT	SCALE	SHEET	TITLE:
mm		1 of 1	<b>6.35mm PITCH 180° SINGLE ROW WAFER, FEMALE TYPE</b>
DRAWN BY 李勤 2006.02.25	APPROVED BY 董正一 2006.02.25	DRAW NO. : C6350WV-XPV0	
GENERAL TOLERANCE		REV. A1	
A1	REVISE	2007.09.14	X. X±0.25
A0	NEW RELEASE	2006.02.25	X. XX±0.15
REV.	DESCRIPTION	DATE	X. XXX±0.05

