



**SPECIFICATIONS**

Current Rating: 0.5A AC,DC  
 Voltage Rating: 50V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 30mΩ Max.  
 Insulation Resistance: 500MΩ Min.  
 Withstanding Voltage: 500V AC/minute  
 Pin Material: Phosphor Bronze/Tin-plated  
 Material: Nylon 9T,UL94V-0  
 Color: Natural(Black)

**Ordering Information & Dimensions**

PART NO.	Dimensions		PART NO.	Dimensions	
	A	B		A	B
F1000WV-S-04P	3.00	7.80	F1000WV-S-20P	19.00	23.80
F1000WV-S-05P	4.00	8.80	F1000WV-S-21P	20.00	24.80
F1000WV-S-06P	5.00	9.80	F1000WV-S-22P	21.00	25.80
F1000WV-S-07P	6.00	10.80	F1000WV-S-23P	22.00	26.80
F1000WV-S-08P	7.00	11.80	F1000WV-S-24P	23.00	27.80
F1000WV-S-09P	8.00	12.80	F1000WV-S-25P	24.00	28.80
F1000WV-S-10P	9.00	13.80	F1000WV-S-26P	25.00	29.80
F1000WV-S-11P	10.00	14.80	F1000WV-S-27P	26.00	30.80
F1000WV-S-12P	11.00	15.80	F1000WV-S-28P	27.00	31.80
F1000WV-S-13P	12.00	16.80	F1000WV-S-29P	28.00	32.80
F1000WV-S-14P	13.00	17.80	F1000WV-S-30P	29.00	33.80
F1000WV-S-15P	14.00	18.80	F1000WV-S-31P	30.00	34.80
F1000WV-S-16P	15.00	19.80	F1000WV-S-32P	31.00	35.80
F1000WV-S-17P	16.00	20.80	F1000WV-S-33P	32.00	36.80
F1000WV-S-18P	17.00	21.80	F1000WV-S-34P	33.00	37.80
F1000WV-S-19P	18.00	22.80			

				JOINT TECH ELECTRONIC IND. CO., LTD.	
				JOY DAY INDUSTRIAL CO., LTD.	
UNIT		SCALE	SHEET	TITLE:	
mm			1 of 1		
DRAWN BY		APPROVED BY		1.00mm PITCH FFC/FPC CONNECTOR 180° SMT TYPE, NON-ZIF	
董正一		董正一			
2001.03.21		2001.03.21			
GENERAL TOLERANCE					
B1	REVISE	2008.01.16	X.X ± 0.25	ANGLE ±	DRAW NO. : F1000WV-S-XP
B0	NEW RELEASE	2005.11.19	X.XX ± 0.15		
REV.	DESCRIPTION	DATE	X.XXX ± 0.05		