



SPECIFICATIONS

Current Rating: 0.5A AC,DC
 Voltage Rating: 50V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 30mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Pin Material: Phosphor Bronze/Tin-plated
 Material: Nylon 9T,UL94V-0
 Color: Natural(Black)

Ordering Information & Dimensions

PART NO.	Dimensions		PART NO.	Dimensions	
	A	B		A	B
F1000WV-04P	3.00	7.80	F1000WV-20P	19.00	23.80
F1000WV-05P	4.00	8.80	F1000WV-21P	20.00	24.80
F1000WV-06P	5.00	9.80	F1000WV-22P	21.00	25.80
F1000WV-07P	6.00	10.80	F1000WV-23P	22.00	26.80
F1000WV-08P	7.00	11.80	F1000WV-24P	23.00	27.80
F1000WV-09P	8.00	12.80	F1000WV-25P	24.00	28.80
F1000WV-10P	9.00	13.80	F1000WV-26P	25.00	29.80
F1000WV-11P	10.00	14.80	F1000WV-27P	26.00	30.80
F1000WV-12P	11.00	15.80	F1000WV-28P	27.00	31.80
F1000WV-13P	12.00	16.80	F1000WV-29P	28.00	32.80
F1000WV-14P	13.00	17.80	F1000WV-30P	29.00	33.80
F1000WV-15P	14.00	18.80	F1000WV-31P	30.00	34.80
F1000WV-16P	15.00	19.80	F1000WV-32P	31.00	35.80
F1000WV-17P	16.00	20.80	F1000WV-33P	32.00	36.80
F1000WV-18P	17.00	21.80	F1000WV-34P	33.00	37.80
F1000WV-19P	18.00	22.80			

 JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.					
UNIT	SCALE	SHEET	TITLE:		
mm		1 of 1	1.00mm PITCH FFC/FPC CONNECTOR 180° DIP TYPE, NON-ZIF		
DRAWN BY		APPROVED BY			
董正一 2001.03.21		董正一 2001.03.21			
GENERAL TOLERANCE					
B1	REVISE	2008.01.16	X. X±0.25	ANGLE±	
B0	NEW RELEASE	2005.11.19	X. XX±0.15		
REV.	DESCRIPTION	DATE	X. XXX±0.05		
DRAW NO. : F1000WV-XP				REV. B1	