



### SPECIFICATIONS

Current Rating: 0.5A AC,DC  
 Voltage Rating: 50V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 30mΩ Max.  
 Insulation Resistance: 500MΩ Min.  
 Withstanding Voltage: 500V AC/minute  
 Pin Material: Phosphor Bronze/Tin-plated  
 Housing: Nylon 46,UL94V-0,Natural(Beige)  
 Actuator: Nylon 46,UL94V-0,Brown

### Ordering Information & Dimensions

PART NO.	Dimensions		
	A	B	C
F1002WV-S-04P	3.00	10.00	5.20
F1002WV-S-05P	4.00	11.00	6.20
F1002WV-S-06P	5.00	12.00	7.20
F1002WV-S-07P	6.00	13.00	8.20
F1002WV-S-08P	7.00	14.00	9.20
F1002WV-S-09P	8.00	15.00	10.20
F1002WV-S-10P	9.00	16.00	11.20
F1002WV-S-11P	10.00	17.00	12.20
F1002WV-S-12P	11.00	18.00	13.20
F1002WV-S-13P	12.00	19.00	14.20
F1002WV-S-14P	13.00	20.00	15.20
F1002WV-S-15P	14.00	21.00	16.20
F1002WV-S-16P	15.00	22.00	17.20
F1002WV-S-17P	16.00	23.00	18.20
F1002WV-S-18P	17.00	24.00	19.20
F1002WV-S-19P	18.00	25.00	20.20
F1002WV-S-20P	19.00	26.00	21.20
F1002WV-S-21P	20.00	27.00	22.20
F1002WV-S-22P	21.00	28.00	23.20
F1002WV-S-23P	22.00	29.00	24.20
F1002WV-S-24P	23.00	30.00	25.20
F1002WV-S-25P	24.00	31.00	26.20
F1002WV-S-26P	25.00	32.00	27.20
F1002WV-S-27P	26.00	33.00	28.20
F1002WV-S-28P	27.00	34.00	29.20
F1002WV-S-29P	28.00	35.00	30.20
F1002WV-S-30P	29.00	36.00	31.20
F1002WV-S-31P	30.00	37.00	32.20
F1002WV-S-32P	31.00	38.00	33.20

				JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
		UNIT	SCALE	SHEET	TITLE:
		mm		1 of 1	
		DRAWN BY	APPROVED BY		
		董正一	董正一		
		2002.07.26	2002.07.26		
		GENERAL TOLERANCE			
B1	REVISE	2008.01.16	X.X±0.25	ANGLE±	
B0	NEW RELEASE	2005.11.19	X.XX±0.15		
REV.	DESCRIPTION	DATE	X.XXX±0.05		
					DRAW NO. : F1002WV-S-XP
					REV. B1