


SPECIFICATIONS

Current Rating: 0.5A AC,DC
 Voltage Rating: 50V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 30mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Pin Material: Phosphor Bronze/Tin-plated
 Material: Nylon 9T,UL94V-0
 Color: Natural(Black)

Ordering Information & Dimensions

PART NO.	Dimensions		PART NO.	Dimensions	
	A	B		A	B
F1004WV-04P	3.00	6.50	F1004WV-20P	19.00	22.50
F1004WV-05P	4.00	7.50	F1004WV-21P	20.00	23.50
F1004WV-06P	5.00	8.50	F1004WV-22P	21.00	24.50
F1004WV-07P	6.00	9.50	F1004WV-23P	22.00	25.50
F1004WV-08P	7.00	10.50	F1004WV-24P	23.00	26.50
F1004WV-09P	8.00	11.50	F1004WV-25P	24.00	27.50
F1004WV-10P	9.00	12.50	F1004WV-26P	25.00	28.50
F1004WV-11P	10.00	13.50	F1004WV-27P	26.00	29.50
F1004WV-12P	11.00	14.50	F1004WV-28P	27.00	30.50
F1004WV-13P	12.00	15.50	F1004WV-29P	28.00	31.50
F1004WV-14P	13.00	16.50	F1004WV-30P	29.00	32.50
F1004WV-15P	14.00	17.50	F1004WV-31P	30.00	33.50
F1004WV-16P	15.00	18.50	F1004WV-32P	31.00	34.50
F1004WV-17P	16.00	19.50	F1004WV-33P	32.00	35.50
F1004WV-18P	17.00	20.50	F1004WV-34P	33.00	36.50
F1004WV-19P	18.00	21.50			

		 JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
UNIT	SCALE	SHEET	
mm		1 of 1	
DRAWN BY	APPROVED BY		
董正一	董正一		
	2002.11.28		
B2	EN0911030532	2009.11.03	GENERAL TOLERANCE
B1	REVISE	2008.02.18	X.X±0.25 ANGLE±
B0	NEW RELEASE	2005.11.19	X.XX±0.15
REV.	DESCRIPTION	DATE	X.XXX±0.05

1.00mm PITCH
FFC/FPC CONNECTOR
180° DIP TYPE, NON-ZIF

DRAW NO. : F1004WV-XP	REV. B2
-----------------------	---------