



**SPECIFICATIONS**

Current Rating: 0.5A AC,DC  
 Voltage Rating: 50V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 30mΩ Max.  
 Insulation Resistance: 500MΩ Min.  
 Withstanding Voltage: 500V AC/minute  
 Pin Material: Phosphor Bronze/Tin-plated  
 Housing: Nylon 46,UL94V-0  
 Cap: Nylon 46,UL94V-0,Natural(Beige)  
 Color: Natural(Beige)

**Ordering Information & Dimensions**

PART NO.	Dimensions		PART NO.	Dimensions	
	A	B		A	B
F1005WV-S-04P	3.00	7.10	F1005WV-S-19P	18.00	22.10
F1005WV-S-05P	4.00	8.10	F1005WV-S-20P	19.00	23.10
F1005WV-S-06P	5.00	9.10	F1005WV-S-21P	20.00	24.10
F1005WV-S-07P	6.00	10.10	F1005WV-S-22P	21.00	25.10
F1005WV-S-08P	7.00	11.10	F1005WV-S-23P	22.00	26.10
F1005WV-S-09P	8.00	12.10	F1005WV-S-24P	23.00	27.10
F1005WV-S-10P	9.00	13.10	F1005WV-S-25P	24.00	28.10
F1005WV-S-11P	10.00	14.10	F1005WV-S-26P	25.00	29.10
F1005WV-S-12P	11.00	15.10	F1005WV-S-27P	26.00	30.10
F1005WV-S-13P	12.00	16.10	F1005WV-S-28P	27.00	31.10
F1005WV-S-14P	13.00	17.10	F1005WV-S-29P	28.00	32.10
F1005WV-S-15P	14.00	18.10	F1005WV-S-30P	29.00	33.10
F1005WV-S-16P	15.00	19.10	F1005WV-S-31P	30.00	34.10
F1005WV-S-17P	16.00	20.10	F1005WV-S-32P	31.00	35.10
F1005WV-S-18P	17.00	21.10			

				JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
		UNIT	SCALE	SHEET	TITLE:
		mm		1 of 1	1.00mm PITCH FFC/FPC CONNECTOR 180° SMT TYPE, NON-ZIF
		DRAWN BY	APPROVED BY		
		董正一	董正一		
		2002.07.23	2002.07.23		
B2	EN0911030533	2009.11.03	GENERAL TOLERANCE		DRAW NO. : F1005WV-S-XP
B1	REVISE	2008.02.18	X. X±0.25	ANGLE±	
B0	NEW RELEASE	2005.11.19	X. XX±0.15		
REV.	DESCRIPTION	DATE	X. XXX±0.05		