



**SPECIFICATIONS**  
 Current Rating: 1A AC,DC  
 Voltage Rating: 200V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 20mΩ Max.  
 Insulation Resistance: 500MΩ Min.  
 Withstanding Voltage: 500V AC/minute  
 Pin Material: Phosphor Bronze/Tin-plated  
 Housing: PBT,UL94V-0,Natural(White)  
 Actuator: PBT,UL94V-0,Natural(White)

**Ordering Information & Dimensions**

PART NO.	Dimensions		
	A	B	C
F1257WW-03P	2.50	10.20	5.20
F1257WW-04P	3.75	11.45	6.45
F1257WW-05P	5.00	12.70	7.70
F1257WW-06P	6.25	13.95	8.95
F1257WW-07P	7.50	15.20	10.20
F1257WW-08P	8.75	16.45	11.45
F1257WW-09P	10.00	17.70	12.70
F1257WW-10P	11.25	18.95	13.95
F1257WW-11P	12.50	20.20	15.20
F1257WW-12P	13.75	21.45	16.45
F1257WW-13P	15.00	22.70	17.70
F1257WW-14P	16.25	23.95	18.95
F1257WW-15P	17.50	25.20	20.20
F1257WW-16P	18.75	26.45	21.45
F1257WW-17P	20.00	27.70	22.70
F1257WW-18P	21.25	28.95	23.95
F1257WW-19P	22.50	30.20	25.20
F1257WW-20P	23.75	31.45	26.45
F1257WW-21P	25.00	32.70	27.70
F1257WW-22P	26.25	33.95	28.95
F1257WW-23P	27.50	35.20	30.20
F1257WW-24P	28.75	36.45	31.45
F1257WW-25P	30.00	37.70	32.70
F1257WW-26P	31.25	38.95	33.95
F1257WW-27P	32.50	40.20	35.20
F1257WW-28P	33.75	41.45	36.45
F1257WW-29P	35.00	42.70	37.70
F1257WW-30P	36.25	43.95	38.95
F1257WW-31P	37.50	45.20	40.20
F1257WW-32P	38.75	46.45	41.45

UNIT	SCALE	SHEET	TITLE:		
mm		1 of 1	<b>1.25mm PITCH FFC/FPC CONNECTOR 180 DIP TYPE,ZIF</b>		
DRAWN BY	APPROVED BY				DRAW NO.:
蕭惠風 2002.07.10	董正一 2002.07.22				F1257WW-XP
GENERAL TOLERANCE					
B1	REVISE	2008.02.20	X.X ±0.25	ANGLE ±	
B0	NEW RELEASE	2005.11.21	X.XX ±0.15		
REV.	DESCRIPTION	DATE	X.XXX ±0.05		