



SPECIFICATIONS
 Current Rating: 2A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
 Contact Resistance: 10m Ω Max
 Insulation Resistance: 1000M Ω Min
 Withstanding Voltage: 500V AC/minute
 Material: Nylon 66+GF,UL94V-0
 Color: Natural(Black)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
F2544H-02P-A	2.54	5.08
F2544H-03P-A	5.08	7.62
F2544H-04P-A	7.62	10.16
F2544H-05P-A	10.16	12.70
F2544H-06P-A	12.70	15.24
F2544H-07P-A	15.24	17.78
F2544H-08P-A	17.78	20.32
F2544H-09P-A	20.32	22.86
F2544H-10P-A	22.86	25.40
F2544H-11P-A	25.40	27.94
F2544H-12P-A	27.94	30.48
F2544H-13P-A	30.48	33.02
F2544H-14P-A	33.02	35.56
F2544H-15P-A	35.56	38.10
F2544H-16P-A	38.10	40.64
F2544H-17P-A	40.64	43.18
F2544H-18P-A	43.18	45.72
F2544H-19P-A	45.72	48.26
F2544H-20P-A	48.26	50.80
F2544H-21P-A	50.80	53.34
F2544H-22P-A	53.34	55.88
F2544H-23P-A	55.88	58.42
F2544H-24P-A	58.42	60.96
F2544H-25P-A	60.96	63.50

				JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
		UNIT	SCALE	SHEET	TITLE:
		mm		1 of 1	
		DRAWN BY		APPROVED BY	
		董正一		董正一	
		2004.11.06		2004.11.06	
		GENERAL TOLERANCE			
B2	EN0911050541	2009.11.05			
B1	REVISE	2007.11.30	X.X \pm 0.25	ANGLE \pm	
B0	NEW RELEASE	2005.12.05	X.XX \pm 0.15		
REV.	DESCRIPTION	DATE	X.XXX \pm 0.05		
				DRAW NO. :	REV. B2
				F2544H-XP-A	

**2.54mm PITCH HOUSING,
FFC CONNECTOR, A TYPE**