



**SPECIFICATIONS**

Current Rating: 2A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range:  $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$   
 Contact Resistance: 10m $\Omega$  Max  
 Insulation Resistance: 1000M $\Omega$  Min  
 Withstanding Voltage: 500V AC/minute  
 Material: Nylon 66+GF,UL94V-0  
 Color: Natural(Black)

**Ordering Information & Dimensions**

PART NO.	Dimensions	
	A	B
F2544H-02P-B	2.54	5.08
F2544H-03P-B	5.08	7.62
F2544H-04P-B	7.62	10.16
F2544H-05P-B	10.16	12.70
F2544H-06P-B	12.70	15.24
F2544H-07P-B	15.24	17.78
F2544H-08P-B	17.78	20.32
F2544H-09P-B	20.32	22.86
F2544H-10P-B	22.86	25.40
F2544H-11P-B	25.40	27.94
F2544H-12P-B	27.94	30.48
F2544H-13P-B	30.48	33.02
F2544H-14P-B	33.02	35.56
F2544H-15P-B	35.56	38.10
F2544H-16P-B	38.10	40.64
F2544H-17P-B	40.64	43.18
F2544H-18P-B	43.18	45.72
F2544H-19P-B	45.72	48.26
F2544H-20P-B	48.26	50.80
F2544H-21P-B	50.80	53.34
F2544H-22P-B	53.34	55.88
F2544H-23P-B	55.88	58.42
F2544H-24P-B	58.42	60.96
F2544H-25P-B	60.96	63.50

		JOINT TECH ELECTRONIC IND. CO., LTD.	
		JOY DAY INDUSTRIAL CO., LTD.	
UNIT	SCALE	SHEET	TITLE:
mm		1 of 1	
DRAWN BY	APPROVED BY	2.54mm PITCH HOUSING, FFC CONNECTOR, B TYPE	
董正一	董正一		
2004.11.06	2004.11.06	DRAW NO. :	
GENERAL TOLERANCE		REV. B2	
B2	EN0911050541	2009.11.05	
B1	REVISE	2007.11.30	X.X $\pm$ 0.25
B0	NEW RELEASE	2005.12.05	X.XX $\pm$ 0.15
REV.	DESCRIPTION	DATE	X.XXX $\pm$ 0.05