



SPECIFICATIONS

Current Rating: 2A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
 Contact Resistance: 10m Ω Max
 Insulation Resistance: 1000M Ω Min
 Withstanding Voltage: 500V AC/minute
 Material: Nylon 66+GF,UL94V-0
 Color: Natural(Black)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
F2544H-02P-B	2.54	5.08
F2544H-03P-B	5.08	7.62
F2544H-04P-B	7.62	10.16
F2544H-05P-B	10.16	12.70
F2544H-06P-B	12.70	15.24
F2544H-07P-B	15.24	17.78
F2544H-08P-B	17.78	20.32
F2544H-09P-B	20.32	22.86
F2544H-10P-B	22.86	25.40
F2544H-11P-B	25.40	27.94
F2544H-12P-B	27.94	30.48
F2544H-13P-B	30.48	33.02
F2544H-14P-B	33.02	35.56
F2544H-15P-B	35.56	38.10
F2544H-16P-B	38.10	40.64
F2544H-17P-B	40.64	43.18
F2544H-18P-B	43.18	45.72
F2544H-19P-B	45.72	48.26
F2544H-20P-B	48.26	50.80
F2544H-21P-B	50.80	53.34
F2544H-22P-B	53.34	55.88
F2544H-23P-B	55.88	58.42
F2544H-24P-B	58.42	60.96
F2544H-25P-B	60.96	63.50

						JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
		UNIT	SCALE	SHEET	TITLE:		
		mm		1 of 1	2.54mm PITCH HOUSING, FFC CONNECTOR, B TYPE		
		DRAWN BY 董正一 2004.11.06		APPROVED BY 董正一 2004.11.06			
		GENERAL TOLERANCE					
B1	REVISE	2007.11.30	X.X \pm 0.25	ANGLE \pm		DRAW NO.: F2544H-XP-B	
B0	NEW RELEASE	2005.12.05	X.XX \pm 0.15				
REV.	DESCRIPTION	DATE	X.XXX \pm 0.05				