



**SUGGESTED PCB LAYOUT  
(COMPONENT SIDE)**

1. MATERIAL:  
HOUSING: PBT, BLACK, UL94V-0  
CONTACTS: 0.35[0.014] THICK PHOSPHOR BRONZE PLATED WITH  
100 $\mu$ m MINIMUM THICK TIN IN SOLDER AREA.  
15 $\mu$ m MINIMUM GOLD IN LOCALIZED PLATE AREA.  
ENTIRE CONTACTS PLATED WITH 30 $\mu$ m MINIMUM THICK NICKEL.
2. JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68, SUBPART F.
3. PART NUMBER: HRJ801215-U2688-F2

				JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
		UNIT	SCALE	SHEET	TITLE:
		mm[inch]		1 of 1	DOUBLE STACK MODULAR JACK, 2X6, W/O LED, 8P, 8C, UNSHIELDED, THRU-HOLE
		DRAWN BY	APPROVED BY		
		董正一	董正一		
		2004.08.20	2004.08.20		
		GENERAL TOLERANCE			
		X. X $\pm$ 0.25	ANGLE $\pm$		DRAW NO. : HRJ801215-U2688-F2
		X. XX $\pm$ 0.15			
		X. XXX $\pm$ 0.05			
B0	NEW RELEASE	2005.12.25	X. XX $\pm$ 0.15		REV. B0
REV.	DESCRIPTION	DATE	X. XXX $\pm$ 0.05		