


SUGGESTED PCB LAYOUT  
(COMPONENT SIDE)



1.MATERIAL:

HOUSING: PBT, BLACK, UL94V-0  
CONTACTS: 0.35[0.014] THICK PHOSPHOR BRONZE PLATED WITH  
100μ" MINIMUM THICK TIN IN SOLDER AREA.  
15μ" MINIMUM GOLD IN LOCALIZED PLATE AREA.  
ENTIRE CONTACTS PLATED WITH 30μ" MINIMUM THICK NICKEL.  
SHIELDED: 0.25[0.0098] THICK COPPER ZINC ALLOY PLATED WITH  
30μ" MINIMUM THICK NICKEL.

2.JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68, SUBPART F.

3.PART NUMBER: HRJM15-S1188-X-T-F2

REFER TO LED OPTIONS TABLE FOR ORDERING CODES

				JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
		UNIT	SCALE	SHEET	TITLE:
		mm[inch]		1 of 1	RJ45, MODULAR JACK, 1X1, W/LED, 8P, 8C, SHIELDED, THRU-HOLE
		DRAWN BY	APPROVED BY		
		董正一	謝瑞清		
		2002.02.01	2002.02.01		
		GENERAL TOLERANCE			
		X. X±0.25	ANGLE±		DRAW NO. : HRJM15-S1188-X-T-F2
B0	NEW RELEASE	2005.12.25	X. XX±0.15		
REV.	DESCRIPTION	DATE	X. XXX±0.05		
					REV. B0