


SUGGESTED PCB LAYOUT  
(COMPONENT SIDE)



1. MATERIAL:

HOUSING: PBT, BLACK, UL94V-0  
 CONTACTS: 0.35[0.014] THICK PHOSPHOR BRONZE PLATED WITH  
 100µ" MINIMUM THICK TIN IN SOLDER AREA.  
 15µ" MINIMUM GOLD IN LOCALIZED PLATE AREA.  
 ENTIRE CONTACTS PLATED WITH 30µ" MINIMUM THICK NICKEL.  
 SHIELDED: 0.25[0.0098] THICK COPPER ZINC ALLOY PLATED WITH  
 30µ" MINIMUM THICK NICKEL.

2. JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68, SUBPART F.

3. PART NUMBER: HRJM15-S1488-X-D-F1

REFER TO LED OPTIONS TABLE FOR ORDERING CODES

				JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
		UNIT	SCALE	SHEET	TITLE:
		mm[inch]		1 of 1	RJ45, MODULAR JACK, 1X4, W/LED, 8P, 8C, SHIELDED, THRU-HOLE
		DRAWN BY	APPROVED BY		DRAW NO. :
		董正一	謝瑞清		HRJM15-S1488-X-D-F1
		2002.02.01	2002.02.01		REV. B0
		GENERAL TOLERANCE			
		X. X±0.25	ANGLE±		
B0	NEW RELEASE	2005.12.25	X. XX±0.15		
REV.	DESCRIPTION	DATE	X. XXX±0.05		