


**SUGGESTED PCB LAYOUT  
(COMPONENT SIDE)**



- 1.MATERIAL:**  
 HOUSING: PBT, BLACK, UL94V-0  
 CONTACTS: 0.35[0.014] THICK PHOSPHOR BRONZE PLATED WITH 100µ" MINIMUM THICK TIN IN SOLDER AREA. 15µ" MINIMUM GOLD IN LOCALIZED PLATE AREA. ENTIRE CONTACTS PLATED WITH 30µ" MINIMUM THICK NICKEL.  
 SHIELDED: 0.25[0.0098] THICK COPPER ZINC ALLOY PLATED WITH 30µ" MINIMUM THICK NICKEL.
- 2.JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68, SUBPART F.**
- 3.PART NUMBER: HRJM15-S1488-X-N-F2**

REFER TO LED OPTIONS TABLE FOR ORDERING CODES

				JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
		UNIT	SCALE	SHEET	TITLE:
		mm[inch]		1 of 1	RJ45, MODULAR JACK, 1X4, W/LED, 8P, 8C, SHIELDED, THRU-HOLE
		DRAWN BY	APPROVED BY		DRAW NO. : HRJM15-S1488-X-N-F2
		董正一	謝瑞清		
		2002.02.01	2002.02.01		REV. B0
		GENERAL TOLERANCE			
		X. X±0.25	ANGLE±		
		X. XX±0.15			
		X. XXX±0.05			
B0	NEW RELEASE	2005.12.25			
REV.	DESCRIPTION	DATE			